

**This product may be purchased from Connevens Limited secure online store
at www.DeafEquipment.co.uk**



DeafEquipment.co.uk

Solutions to improve the quality of life



Moldex Hearing Protection.

The Moldex range of plugs and bands

- **Pura-Fit** 7700, Pura-Fit Cord 6900 • **Spark Plugs soft** 7800, Spark Plugs soft (PocketPak) 7802, Spark Plugs soft (Cord) 7801
- **Rockets** 6400, Rockets Cord 6401, Rockets Detect 6409 • **Pura-Band** 6600 • **Jazz-Band** 6700, Jazz-Band replacement pods 6750
- **MoldexStation**: Pura-Fit (250 pairs) 7725, Pura-Fit (500 pairs) 7750, Spark Plugs soft (250 pairs) 7825, Spark Plugs soft (500 pairs) 7850

Characteristics

The Moldex range of hearing protection products provide a wide range of options to cover all your hearing protection requirements.

From high attenuation ear plugs such as the "Pura-Fit" and "Spark Plugs soft", reusable ear plugs such as the "Rockets", including the Rockets Detectable through to banded ear plugs, the "Jazz-Band" and "Pura-Band" for intermittent noise, all requirements are covered.

All Moldex hearing products have been designed with the user in mind, and high levels of comfort have been engineered in to the products without compromising the optimal protection.

The Moldex hearing products are available in basic paper or plastic wrappers, or "PocketPak" and "MoldexStation" for individual dispensing solutions.

Construction / Materials

Moldex Hearing Products are made of:

- Pura-Fit, Spark Plugs soft = Polyurethane
- Rockets = Kraton, PVC
- Rockets Detect = Kraton, PVC, Metal (Iron)
- Cord, all versions = PVC
- Pura-Band = Kraton, Polypropylene
- Jazz-Band = Polyurethane, Polycarbonate, Polyester-cord
- PocketPak = 3BC-Polymer
- MoldexStation = 3BC-Polymer

Weights:

- PURA-FIT (per pair):
- 7700: 1 g 6900: 2 g
- SPARK PLUGS SOFT (per pair):
- 7800: 1 g 7801: 2 g
- 7802: 9 g (two pairs including PocketPak)
-
- ROCKETS (per pair including PocketPak):
- 6400: 9 g 6401: 10 g 6409: 11 g
-
- JAZZ-BAND::
- 6700: 20 g
-
- PURA-BAND:
- 6600: 11 g

Certification

The Moldex range of plugs and bands for hearing protection meet the requirements of EN352-2: 1993 and are CE-Marked in accordance with the requirements of European Directive 89/686/EEC.

The BIA (0121) in St. Augustin in Germany is the body responsible for type examination (Article 10) of all products, apart from "Spark Plugs soft" as they are certified by FIOH (0403) in Helsinki (Finland).

The products are manufactured in an ISO 9001 certified plant.

Attenuation Data

The Moldex range of hearing protection passes the EN 352-2 minimum attenuation requirements set out in the table below. The A.P.V. values (M_f - S_f) of the ear-plugs and bands must exceed the data in the table. Below that is presented the full attenuation data tables for the Moldex products.

Minimum attenuation requirement (dB)								
Freq. (Hz)	63	125	250	500	1000	2000	4000	8000
A.P.V (dB)	-	5.0	8.0	10.0	12.0	12.0	12.0	12.0

Pura-Fit (7700), Pura-Fit Cord (6900)								
Freq. (Hz)	63	125	250	500	1000	2000	4000	8000
M_f (dB)	20.0	26.2	33.1	38.0	39.0	34.3	42.3	43.3
S_f (dB)	6.0	6.2	8.1	6.1	3.8	2.5	3.4	5.5
A.P.V (dB)	14.0	20.0	25.0	31.9	35.2	31.8	38.9	37.8
Sizes: 6-12	H = 34 dB		M = 32 dB		L = 26 dB		SNR = 34 dB	

Spark Plugs soft (7800), Spark Plugs soft Cord (7801)								
Freq. (Hz)	125	250	500	1000	2000	4000	8000	
M_f (dB)	36,0	36,7	39,0	36,0	37,0	46,7	44,6	
S_f (dB)	6,0	6,1	6,5	5,9	4,9	3,2	3,8	
A.P.V (dB)	30,0	30,6	32,5	30,1	32,1	43,5	40,8	
Sizes: 6-12	H = 34 dB		M = 32 dB		L = 31 dB		SNR = 35 dB	

Rockets (6400), Rockets Cord (6401), Rockets Detect (6409)								
Freq. (Hz)	63	125	250	500	1000	2000	4000	8000
M_f (dB)	24.0	25.9	25.3	26.4	25.0	32.2	35.6	41.6
S_f (dB)	5.3	4.0	6.6	6.8	5.9	3.4	3.2	4.8
A.P.V (dB)	18.7	21.9	18.6	19.6	19.1	28.8	32.4	36.8
Sizes: 7-12	H = 27 dB		M = 21 dB		L = 20 dB		SNR = 25 dB	

Jazz-Band (6700)								
Freq. (Hz)	63	125	250	500	1000	2000	4000	8000
M_f (dB)	24.8	25.1	21.4	19.2	23.3	29.4	35.8	35.7
S_f (dB)	3.9	4.2	3.1	4.0	3.5	5.1	5.2	6.1
A.P.V (dB)	20.9	20.9	18.3	15.2	19.8	24.3	30.6	29.6
Sizes: 9-14	H = 25 dB		M = 19 dB		L = 18 dB		SNR = 23 dB	

Pura-Band (6600)								
Freq. (Hz)	63	125	250	500	1000	2000	4000	8000
M_f (dB)	23.7	23.8	22.4	18.0	21.3	28.6	37.3	30.1
S_f (dB)	7.6	4.9	3.5	3.5	4.4	4.5	5.2	6.5
A.P.V (dB)	17.2	18.6	17.9	13.6	17.8	25.1	32.4	22.5
Sizes: 6-13	H = 24 dB		M = 18 dB		L = 17 dB		SNR = 22 dB	



M a d e b y



Moldex Hearing Protection.

Testing

The earplugs and bands of the Moldex Hearing Protection range have been tested to EN 352-2 and fulfill all requirements of the relevant categories.

• Ignitability

The ear plugs or banded earplugs shall not ignite upon application of a heated rod, nor continue to glow after the removal of the heated rod.


• Construction


All parts of the ear plugs and banded ear plugs are designed and manufactured so that they are not liable to cause physical damage to the wearer when fitted and used according to the instructions.


Instructions For Use


- The plugs and banded plugs must be used in accordance with the relevant national legislation.
- Warning: disregarding the instructions for use and fitting instructions for these products can affect the product efficiency in protecting against noise.
- The products should be stored in a cool, dry environment.
- The products may be adversely affected by direct contact with certain chemical substances (e.g. aromatical hydrocarbons).
- "Pura-Fit" and "Spark Plugs soft" are for single use only.
- "Rockets", "Jazz-Band" and "Pura-Band" are reusable provided the hygiene of the product is maintained between uses. Clean with mild soap and water.


Instructions For Fitting "Pura-Fit" and "Spark Plugs soft"

- 


Roll the plugs between the finger and thumb to compress them for insertion.
- 


Reach above the head and pull the ear gently upwards.
- 


Slide the plug into the ear canal and hold in place for 10 seconds to let the plug expand and fill the ear.
- 

The plug will then be correctly positioned in the ear canal ensuring it offers maximum hearing protection.
- 

Instructions For Fitting "Rockets"


- 


Reach above the head and pull the ear gently upwards.
- 


Grip the plastic handle of the Rocket plug and slide the plug into the ear canal. Rotating the plug slightly whilst inserting may help.
- 

The plug will then be correctly positioned in the ear canal ensuring it offers maximum hearing protection.

Instructions For Fitting "Pura-Band" and "Jazz-Band"

- 

Place band under chin and gently insert pods into ear canal.
- 

Ensure tip of pod is located in ear canal. Grasp top of ear, pull upwards and gently push pod into ear.
- 

Only for Jazz-Band:
During work breaks let band hang around the neck.

INFO:

For help on selection and training please contact us. We offer a wide range of training packages and support material.



M a d e b y